



ESBE Scientific



BACK TO THE LAB

PRICE PROMOTION



Vortex Mixer, Mini Analog OHS-30392115

\$395

OHAUS Mini Vortex Mixer used for gentle to high-speed reliable mixing. The analog model offers a variable speed control.

SPECIFICATIONS

Control:	Analog
Duty Rating:	Intermittent
Orbit:	0.2 in (4.9 mm)
Speed Range:	300 rpm – 3200 rpm
Capacity:	0.5 kg
Dimensions:	6.5 in x 8.3 in x 4.8 in (16.5 cm x 21 cm x 12.3 cm)
Net Weight:	9.7 lb (4.4 kg)
Power:	120V, 1.2A, 50/60Hz



Vortex Mixer, Microplate OHS-30392162

\$600

OHAUS Microplate Vortex Mixers are perfect for mixing microplates throughout the speed range. All models are designed for continuous-duty use in the lab.

SPECIFICATIONS

Control:	Analog
Duty Rating:	Continuous
Orbit:	0.1 in (3.5 mm)
Speed Range:	On Mode, 300 rpm – 2500 rpm; Touch Mode, 300 rpm – 3500 rpm
Capacity:	2 Microplates
Dimensions:	4.5 in x 10.5 in x 5.4 in (11.4 cm x 26.7 cm x 13.7 cm)
Net Weight:	11.7 lb (5.3 kg)
Power:	120V, 0.25A, 50/60Hz

PROMO VALID UNTIL NOVEMBER 30, 2020
CONTACT YOUR LOCAL ESBE REPRESENTATIVE FOR MORE DETAILS
OR VISIT ESBE.COM



ESBRITE Laboratory
Detergent, 1.36 kg

ESB-ES10001B

\$8.95



ESBE Scientific
80 McPherson Street
Markham, Ontario, L3R 3V6

Web: www.esbe.com
Toll free: 1.800.268.3477
Email: info@esbe.com



Promo valid until November 30, 2020. Prices/specifications are current at the time of printing/publishing, subject to change without notice and are not to be combined with other offers/discounts or contract pricing. While quantities last.



ESBE Scientific



BACK TO THE LAB

PRICE PROMOTION



MINI Centrifuge

OHS-30134157

\$230

The OHAUS MINI Centrifuge is a small but powerful mini centrifuge for simple and quick liquid separation. With an 8 place 1.5/2mL tube rotor as well as a 4 place PCR 8-strip tube rotor.

SPECIFICATIONS

Speed Range:	0 rpm – 6,000 rpm
Max Centrifuge Force:	2,000 g
Max Capacity:	8 x 1.5 / 2.0 ml
Rotor included:	Angle rotor 8 x 1.5 ml / 2.0 ml Angle rotor 4 x 8 place PCR Strips
Lid lock:	Mechanical
Noise Level:	$\geq 60 \pm 2$ dB(A)
Power:	100 - 240 V
Running Time:	Continuous
Power:	120V, 1.2A, 50/60Hz



Shaker, Light Duty

OHS-30391912

\$1700

Dependable OHAUS Light Duty Shakers are designed for applications with loads up to 3.6kg. Non-digital economical unit for everyday shaking and triple eccentric drive systems for stable shaking with microprocessor-control for reliable shaking action.

SPECIFICATIONS

Motion:	Orbital, 15 mm
Capacity:	3.6 kg
Speed Range:	40 rpm – 300 rpm
Tray Size (LxW):	11.75 in x 8.75 in (29.9 cm x 22.2 cm)
Control:	Digital
Drive System:	Brushless DC Motor; Triple Eccentric
Orbit:	0.6 in (15 mm)
Timer:	1 second – 160 hours
Tray Construction:	Aluminum

PROMO VALID UNTIL **NOVEMBER 30, 2020**

CONTACT YOUR LOCAL ESBE REPRESENTATIVE FOR MORE DETAILS

OR VISIT **ESBE.COM**



ESBRITE Laboratory
Detergent, 1.36 kg

ESB-ES10001B

\$8.95



ESBE Scientific
80 McPherson Street
Markham, Ontario, L3R 3V6

Web: www.esbe.com
Toll free: 1.800.268.3477
Email: info@esbe.com



Promo valid until November 30, 2020. Prices/specifications are current at the time of printing/publishing, subject to change without notice and are not to be combined with other offers/discounts or contract pricing. While quantities last.